



## 365 X-Torq

Husqvarna 365 is a saw for typical professional use. It has been developed in close cooperation with professional users working in the most demanding conditions. The low weight and high power are combined with a rugged engine, making this saw exceptionally versatile and suited for a wide variety of applications.

The X-TORQ® engine gives you a much more environment friendly saw with radically lower exhaust emission level and fuel consumption.



### X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



### MAGNESIUM CRANKCASE

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



### LOWVIB®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

## Features

- Quick-release air filter
- Smart Start® for easy starting
- Adjustable chain oil pump
- Quick and easy chain adjustment
- Easy to maintain with snap locked filter cover
- Maximum durability for tough applications
- Ergonomic grip with angled front handle
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	70.7 cm <sup>3</sup> / 4.31 cu.inch
Power output	3.6 kW
Maximum power speed	10200 rpm
Maximum recommended engine speed	13300 rpm
Fuel tank volume	0.77 lit/26.04 fl oz
Fuel consumption	426 g/kWh
Idling speed	2700 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.5 mm/0.02"
Torque, max.	3.8 Nm/6600 rpm
Oil tank volume	0.42 lit/0.89 US pint
Oil pump type	Automatic
Oil pump capacity	4-20 ml/min
Equivalent vibration level (ahv, eq) front/ rear handle	4/5.4 m/s <sup>2</sup>
Sound pressure level at operators ear	110 dB(A)
Sound power level, guaranteed (LWA)	119 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	41-71 cm/16"-28"
Chain speed at max power	22.7 m/s/74.48 fts
Chainingauge	0.058"
Weight(excl.cutting equipment)	6.4 kg / 14.11 lbs

### ARTICLES

966 42 83-18	18" - 3/8" - H42 - CE - Europe	£ 608.33	£ 729.99
966 42 83-20	20" - 3/8" - H42 - CE - Europe	£ 616.66	£ 739.99

