



372 XP® X-TORQ

A true professional saw in the larger mid-size class, built for very demanding applications. Equipped with X-TORQ® engine with reduced fuel consumption and exhaust emissions. The crankcase and crankshaft are extra heavy-duty and the carburettor has vibration damping in order to handle high speeds and high loads. The saw combines low weight, high power and rapid acceleration with flexible operation.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



ADJUSTABLE OIL PUMP

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.



QUICK-RELEASE AIR FILTER

Facilitates cleaning and replacement of the air filter.

Features

- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands
- Smart Start® for easy starting
- Ergonomic grip with angled front handle
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	70.7 cm ³ / 4.31 cu.inch
Power output	4.1 kW
Maximum power speed	10200 rpm
Maximum recommended engine speed	13500 rpm
Fuel tank volume	0.77 lit/26.04 fl.oz
Fuel consumption	426 g/kWh
Idling speed	2700 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.5 mm/0"
Torque, max.	3.8 Nm/6600 rpm
Oil tank volume	0.42 lit/0.89 US pint
Oil pump type	Automatic
Oil pump capacity	4-20 ml/min
Equivalent vibration level (ahv, eq) front/ rear handle	4/5.4 m/s ²
Sound pressure level at operators ear	110 dB(A)
Sound power level, guaranteed (LWA)	119 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	41-71 cm/16"-28"
Chain speed at max power	22.7 m/s / 74.5 ft/s
Chainingauge	0.058"
Weight(excl.cutting equipment)	6.4 kg / 14.11 lbs

ARTICLES

965 96 81-18	18" - SN - 3/8" - H42 - CE	£ 770.83	£ 924.99
965 96 81-20	20" - SN - 3/8" - H42 - CE	£ 779.16	£ 934.99
965 96 81-44	24" - RSN - 3/8" - H42 - CE	£ 791.66	£ 949.99

