



555

Husqvarna 555 is developed for demanding work by contractors and land owners. The saw has a ground breaking design and is loaded with raw power for efficient operation. Our unique X-Torq® engine technology provide more power where you need it, up to 20% less fuel consumption and 75% less exhaust emission.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



LOWVIB®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

Features

- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Maximum durability for tough applications
- Smart Start® for easy starting
- Felling marks for correct felling direction
- Fuel level window
- Fuel pump for easy starting
- The retaining function prevents losing the bar nuts.
- Increased safety, inertia activated chain brake

Technical data

| | |
|--|------------------------------------|
| Cylinder displacement | 59.8 cm ³ / 3.6 cu.inch |
| Power output | 3.1 kW |
| Maximum power speed | 9600 rpm |
| Maximum recommended engine speed | 13600 rpm |
| Fuel tank volume | 0.65 lit / 21.98 fl oz |
| Fuel consumption | 438 g/kWh |
| Idling speed | 2800 rpm |
| Spark plug | NGK CMR6H |
| Electrode gap | 0.5 mm / 0" |
| Torque, max. | 3.51 Nm / 6100 rpm |
| Oil tank volume | 0.33 lit / 0.7 US pint |
| Oil pump type | Adjustable flow |
| Oil pump capacity | 6-15 ml/min |
| Equivalent vibration level (ahv, eq) front / rear handle | 2.7/3.2 m/s ² |
| Sound pressure level at operators ear | 106 dB(A) |
| Sound power level, guaranteed (LWA) | 118 dB(A) |
| Chain pitch | .325" |
| Recommended bar length, min-max | 33-61 cm / 13"-24" |
| Chain speed at max power | 21.3 m/s / 69.9 fts |
| Chain gauge | 0.058" |
| Weight (excl. cutting equipment) | 5.6 kg / 12.35 lbs |

| ARTICLES | | | |
|--------------|---|----------|----------|
| 966 01 09-15 | 15" - .325" - H25 - CE - Europe,others (44µ air filter General purpose) | £ 574.99 | £ 689.99 |
| 966 01 09-18 | 18" - .325" - H25 - CE - Europe,others (44µ air filter General purpose) | £ 583.33 | £ 699.99 |

